



PRODUCT CATALOGUE



VOLUME 28

Flextool Drive Units

Flextool Drive Units are fitted with a quick action coupling for quick and easy connection of a wide range of flexible shaft submersible pumps and concrete vibrators. They are available with petrol or diesel engines to suit any specific job site requirement.

FLEXTOOL DRIVE UNITS ARE COMPATIBLE WITH ALL FLEXSHAFT PUMPS AND CONCRETE VIBRATORS FITTED WITH A 3-TOOTH DRIVE COUPLING.



Lifting hook for easy and safe onsite handling.

Honda 4-stroke engine for hassle free operation and low engine emissions (petrol models only).

Durable heavy duty motor protection frame.

Heavy duty rubber mounts for vibration isolation (excludes Standard FDU-P1 model).

Dished steel base for easy mobility over concrete reinforcing mesh (Standard FDU-P1 and Super FDU-P2 models only).



Super Drive Unit FDU-P2

POWERED by **HONDA**

PETROL DRIVE UNITS

Petrol drive units are available with Honda four-stroke motors. An oil level sensor is fitted to protect the motor from a lack of crankcase oil.

APPLICATIONS

- Compatible with Flextool Submersible Pumps and Flextool Flexshaft Concrete Vibrators
- Construction, hire industry & manufacturing industry



FDU-P1 (Standard)



FDU-P2 (Super)



FDU-P3 (Heavy Duty)

Model	Operating Weight (kg)	Engine Speed (rpm)	Vibration Isolating Mounts	Lifting Hook	Engine Make	Engine Model	Max Rated Power (Hp)	Fuel Type	Product Code	Barcode
FDU-P1 (Standard)	28.5	3000	No	Yes	Honda	GX160	5.5	P	FT201802-UNIT	9300611599469
FDU-P2 (Super)	32	3000	Yes	Yes	Honda	GX160	5.5	P	FT201798-UNIT	9300611599421
FDU-P3 (Heavy Duty)	38.5	3000	Yes	Yes	Honda	GX270	9	P	FT201799-UNIT	9300611599438

DIESEL DRIVE UNITS

Diesel drive units are ideal for unattended operation and long term reliability. Available in both recoil or key start for easy operation.

APPLICATIONS

- Compatible with Flextool Submersible Pumps and Flextool Flexshaft Concrete Vibrators
- Hazardous areas including mining, tunnels & refineries



FDU-D2 (Diesel)





FDU-DE2 (Diesel Electric Start)

Model	Operating Weight (kg)	Engine Speed (rpm)	Vibration Isolating Mounts	Lifting Hook	Engine Make	Engine Model	Max Rated Power (Hp)	Fuel Type	Product Code	Barcode
FDU-D2 (Diesel)	38	3000	Yes	Yes	Yanmar	L48	4.8	D	FT201800-UNIT	9300611599445
FDU-DE2 (Diesel Electric Start)	52	3000	Yes	Yes	Yanmar - Elec	L48	4.8	D	FT201819-UNIT	9300611599643

Flextool Pumps

Flextool Pumps are highly efficient submersible units which are operated by petrol or diesel portable drive units. Flextool pumps are completely self-priming and extremely robust in their design. The flexible shaft drive facilitates use in many situations where close coupled pumps would not be suitable. The new FP212 series now come with flexshaft support springs which protect the drive shaft when operating over the sharp edge of excavations, pits, dams, etc.



GENERAL PURPOSE PUMPS

APPLICATIONS

- Excavations pits
- Construction sites
- Pier holes
- Dams
- Swimming pools
- Trenches



Clean Water



Water with Debris



Model	Flexshaft Length (m)	Operating Weight (kg)	Shaft Inner Core Diameter (mm)	Shaft Casing Diameter (mm)	Discharge Diameter (mm)	Max Discharge Head (m)	Max Discharge (l/h)	Solids Capacity (mm)	Product Code	Barcode
FP212G-6	6	26.5	13	32	50	26	63,000	28	FT201801-UNIT	9300611599452
FP212G-9	9	38	13	32	50	26	63,000	28	FT201803-UNIT	9300611599483

ABRASION RESISTANT PUMPS

APPLICATIONS

- Quarries
- Sandy soils
- Sand pits
- Slurry



Slurry Water with Fine Particles



Model	Flexshaft Length (m)	Operating Weight (kg)	Shaft Inner Core Diameter (mm)	Shaft Casing Diameter (mm)	Discharge Diameter (mm)	Max Discharge Head (m)	Max Discharge (l/h)	Solids Capacity (mm)	Product Code	Barcode
FP212A-6	6	34	15	38	50	26	63,000	28	FT201805-UNIT	9300611599506
FP212A-9	9	42.5	15	38	50	26	63,000	28	FT201818-UNIT	9300611599636

CHEMICAL RESISTANT PUMPS*

APPLICATIONS

- Anodisers
- Industrial waste
- Salty water
- Others



Other



*Improved chemical resistance to a wide range of chemicals compared to general purpose pumps.

Model	Flexshaft Length (m)	Operating Weight (kg)	Shaft Inner Core Diameter (mm)	Shaft Casing Diameter (mm)	Discharge Diameter (mm)	Max Discharge Head (m)	Max Discharge (l/h)	Solids Capacity (mm)	Product Code	Barcode
FP212C-6	6	37.5	15	38	50	26	63,000	28	FT201817-UNIT	9300611599629

LAY FLAT HOSE

Lay Flat Hose is a lightweight, reinforced PVC that can roll flat and save space.



Hose Type	Length (m)	Hose Diameter (mm) (in)	Fitted With	Product Code	Barcode
Blue - Std Duty	20	50 (2)	Coupling & Joiner	FT200032-UNIT	 9330221047395

FLEXTOOL EXTENSION FLEXSHAFTS

Flextool Extension Flexshafts extend the length of submersible pumps and concrete vibrators. Fitted with the same 60mm quick action coupling as the drive units, these extensions allow for quick onsite connection. Compatible with all Flextool Submersible Pumps and Flexshaft Concrete Vibrators.



APPLICATIONS

- Deep columns
- Elevated formwork
- Deep excavations

Model	Flexshaft Length	Operating Weight (kg)	Shaft Inner Core Diameter (mm)	Shaft Outer Casing Diameter (mm)	Product Code	Barcode
FES-2	6	20	13	32	FT201804-UNIT	 9300611599490



CELEBRATING

50

YEARS OF EXPERIENCE

**EXPERIENCE INNOVATIVE
THINKERS AND PRODUCTS**



ALL ABOUT EXPERIENCE

allpumps.com.au

1300 255 786 | sales@allpumps.com.au