

6GSUBHD16 HIGH PRESSURE DEWATERING



Global Pump® portable electric submersible pumps are ideal for corrosive and abrasive applications.

The Model 6GSUBHD16 pump with 4" NPT and a 16 hp (12 kW) motor is ideal for low volume, high head applications.

FEATURES

Stainless steel strainer, shaft, impeller, outlet and hardware for maximum corrosion resistance

Mechanical seals in wholly enclosed pressure compensated oil chamber

Nitride hardened 410 stainless steel impeller for abrasive applications

Tandem tungsten carbide/tungsten carbide and tungsten carbide/tungsten carbide mechanical seals

Field adjustable nitrile rubber-lined diffuser/wearplate optimizes efficiency throughout the life of the pump

Equipped with sacrificial zinc anodes for maximum life in a saline fluid environment




OPTIONS

Choice of impeller materials including 316 stainless steel for sea water and corrosive applications

Available in complete 316 stainless steel construction with silicon carbide/silicon carbide mechanical seals and viton elastomers

Automatic ON/OFF/ON thermal overloads embedded in stator winding (requires 6 core or control cable and external controls)

Polyurethane diffusers and wearplates available



SPECIFICATIONS	
Size	6" (150 mm)
Power	16 hp (12 kW)
Max Flow	300 gpm (191 m ³ /h)
Max Head	260' (79 m)
Motor	2-pole induction continuous rated motor with squirrel cage rotor. Stator insulation class 'H' (180°C)
Speed (motor)	3,400 RPM @ 60 Hz, 2,800RPM @ 50Hz
Power Rating (motor)	16 hp @ 60 Hz, 12 kW @ 50 Hz Full Load
Current FLA (motor)	22 Amps @ 460v, 25 Amps @ 400v
Max. temperature of the pump liquid (motor)	104°F/40°C
Max. start/stop per hour (motor)	15 Start: Delta starting optional
Power Supply	3 phase, 50/60 Hz, AC Supply. Available in any voltage frequency combination (208/220/230/380/415/460/575/1,000V)
Power Cable	50' (15 m) length standard
pH Range	5 - 8
Submergence	Submergence below liquid surface min. 5" (127 mm) max. 50' (15 m)
Weight (approx. w/o cable)	310 lbs. (140 Kg)

PUMP MATERIAL	
Outer Casing	Epoxy-coated aluminum
Stator Casing	Epoxy-coated extruded aluminum
Diffuser/Wearplate	Nitrile rubber-lined (polyurethane optional)
Shaft	431 Stainless steel
Shaft Seal	Tandem tungsten carbide/tungsten carbide and tungsten carbide/tungsten carbide mechanical seals wholly enclosed in an oil chamber
Hardware	304 Stainless Steel
Impeller	Nitride-hardened 410SS to 56HRC (Standard)
Ball Bearings	Two single row deep groove ball bearing. Bearings enclosed with high temperature grease-containing special anti-corrosion additive
Power Cable	Waterproof/oil proof, rubber-insulated, neoprene-sheathed copper conductor flexible cable. Type SOOW in North America, EPR in the Middle East and HO7RN in the EU. 6 Core or Control cable with thermal overloads optional
Strainer	304 Stainless Steel with 0.375" (10 mm) round holes



GLOBAL PUMP
 10162 East Coldwater Road, Davison, MI 48423
 Tel: 810.653.4828 Fax: 810.658.0632
1.866.360.PUMP www.globalpump.com