

GET MORE OUT OF YOUR BIOGAS SYSTEM

The new, optimised X-UNIT generates **more energy** from the same feed, at the same time providing **greater protection** from harmful contaminants.



WANGEN




MAX. FLOW VOLUME m ³ /h	1.250*
MAX. SPEED CUTTING BLADE min ⁻¹	3.000
MAX. DIFF. PRESSURE bar	6

* Figures apply with water as the medium

CUTS EXTREMELY WELL AND RUNS LIKE CLOCKWORK



Modular, process-optimised and very durable:
the new WANGEN X-UNIT.





WANGEN



X UNIT



Substrate before:
coarse medium interspersed
with contaminants



Substrate after:
finely chopped, porridge-like
medium containing
no contaminants

XTRACT



X CUT

Low wear costs and low energy consumption optimise the efficiency of your system.

- **Low energy consumption** coupled with maximum substrate yield.
- **Durable, heavy-duty seal** with in-house developed cooling and lubricating function for extremely high-performance (up to 6 bar media-pressure).
- Cutting unit with rotating cutting blades speeds of up to **3,000 rpm** provide for excellent substrate digestion rates.
- **Large settling tank** with a large opening for the removal of foreign matter.
- Foreign matter is removed from the medium **without additional energy consumption**.
- **The ultimate ease of servicing**, thanks to rapid replacement of the cutting blade and sealing unit.
- **Galvanised components** for perfect, proven WANGEN-quality corrosion protection throughout.