


## 5H Series

#### **Check Valve Dispensing Pump**



Model		Plunger Diameter		Stroke	Maximum Dispensing	Cycle	Air Consumption	Weight	
Pneumatic	Servo	Inch	mm	Inch (mm)	Volume (cc)	Speed (cpm) <sup>C</sup>	scfm (I/min)	lbs (kg)D	
5H3-C-100	5S3-C-100	1-5/8	41.28		102		13.09 (370) <sup>A</sup>	60 (27.21)	
5H3-C-250	5S3-C-250	2-3/4	69.85	2.00 (76.20)	292	0-30 <sup>C</sup>			
5H3-C-500	5S3-C-500	3-3/4	95.25	3.00 (76.20)	543				
5H3-C-1000	5S3-C-1000	5-1/8	130.18		1014	-			
5H6-C-1500	5S6-C-1500	4-1/2	114.3	C 00 (152 4)	1563	0-12 <sup>C</sup>	10.47 (296) <sup>B</sup>	64 (29.03)	
5H6-C-2000	5S6-C-2000	5-1/8	130.18	6.00 (152.4)	2028	0-120			

5H SERIES

<sup>A</sup> Calculated at full stroke at 30 cpm, 75 psi <sup>B</sup> Calculated at full stroke at 12 cpm, 75 psi <sup>c</sup> Maximum cycle rate is application dependant <sup>D</sup> Pneumatic Drive Only



### **5H Series**


#### **Check Valve Dispensing Pump**

Fittings					
Туре	Size				
Type	Inlet	Outlet			
Sanitary	3/4 - 1	3/4 - 1			
Swage	1/4 - 3/4	3/4			
Tube	1/4 - 3/4	3/4			
Hose	1/4 - 1	1/4 - 1			
	16-28mm	16-28mm			

O-rings & U-cups					
O-rings	U-cup Seals				
Viton	Teflon				
EP	UHMW				
Silicon					
Buna					
Perfluor (Kalrez ®)					

Units: Inches unless specified

Contact Your HIFE Representative for Servo Drive Dimensions



Model		External Dimensions Inch (mm)							
Pneumatic	Servo	A	В	с	D	E	F	G	н
5H3-C-100	5S3-C-100	6.38 (162.05)	8.81 (223.77)	23.77 (603.76)	3.00 (76.20)	1.50 (38.10)	3.50 (88.90)	M8Z1.25	Ø 0.316 +0.002
5H3-C-250	5S3-C-250								
5H3-C-500	5S3-C-500								
5H3-C-1000	5S3-C-1000								
5H6-C-1500	5S6-C-1500			29.07 (738.4)					
5H6-C-2000	5S6-C-2000								

# CELEBRATING

### **YEARS OF EXPERIENCE**

# **EXPERIENCE INNOVATIVE THINKERS AND PRODUCTS**



ALL ABOUT EXPERIENCE allpumps.com.au

1300 255 786 | sales@allpumps.com.au