

# **Rotary Valve Dispensing Pump**

### **Dispense Volume** 100-2000ml

Viscosity Medium to High (>20,000 cps)

### **Applications**

The product can be used in a wide range of industries, including consumer products, cosmetics, chemical, technical, and pharmaceutical products.



### **Details**

Electric or Pneumatic Start Signal

Fine Adjustment Speed Control

Precision Pneumatic High speed Rotary

Precision Volumetric Adjustment

Precision Servo Drive and Motor Available

Programmable Servo Speed Profiling

Inlet & Outlet Fittings

Actuator

Configurable

Internal Full Stroke Sensor Precision Pneumatic Drive

316L Stainless Steel Construction Other Materials of Construction available

High Acci	uracy
+/- 0.5%	or Better

Model		Plunger Diameter		Stroke	Maximum Dispensing	Cycle	Air Consumption	Weight	
Pneumatic	Servo	Inch	mm	inch (mm)	Volume (cc)	Speed (cpm) <sup>C</sup>	scfm (I/min)	lbs (kg) <sup>D</sup>	
5H3-R-100	5S3-R-100	1-5/8	41.28	3.00 (76.20)	102	0-30 <sup>C</sup>	13.53 (383) <sup>A</sup>	66 (30)	
5H3-R-250	5S3-R-250	2-3/4	69.85		292				
5H3-R-500	5S3-R-500	3-3/4	95.25	5.00 (7.0.20)	543				
5H3-R-1000	5S3-R-1000	5-1/8	130.18		1014				
5H6-R-1500	5S6-R-1500	4-1/2	114.3	6.00 (152.40)	1563	2 126	10.64 (301) <sup>B</sup>	72 (33)	
5H6-R-2000	5H3-R-2000	5-1/8	130.18	0.00 (132.40)	2028	0-12 <sup>C</sup>			

<sup>&</sup>lt;sup>A</sup> Calculated at full stroke at 30 cpm, 75 psi <sup>B</sup> Calculated at full stroke at 12 cpm, 75 psi <sup>C</sup> Maximum cycle rate is application dependant <sup>D</sup> Pneumatic Drive




# **Rotary Valve Dispensing Pump**

Fittings						
Туре	Size					
Type	Inlet	Outlet				
Sanitary	3/4 - 1-1/2	3/4-1-1/2				
Swage	3/4	3/4				
Tube	3/4	3/4				
Hose	1 33mm	1 33mm				

Units: Inches unless specified


O-rings & U-cups					
O-rings	U-cup Seals				
Viton	Teflon				
EP	UHMW				
Silicon					
Buna					
Perfluor (Kalrez ® )					

## **Pneumatic Drive**



Мо	del	External Dimensions Inch (mm)								
Pneumatic	Servo	A	В	С	D	E	F	G	Н	
5H3-R-100	5S3-R-100	9.29 (236.0)								
5H3-R-250	5S3-R-250		9,29 8,79		25.55	4.09	1.09			
5H3-R-500	5S3-R-500			(648.9)	(103.9)	(29.7)	3.50	MOV4 25	Ø 0.316	
5H3-R-1000	5S3-R-1000		(223.3)				(88.90)	M8X1.25	+0.002	
5H6-R-1500	5S6-R-1500			29.07	5.59	2.59				
5H6-R-2000	5S6-R-2000			(738.4)	(142.0)	(65.8)				

Contact Your HIFE Representative for Servo Drive Dimensions



# EXPERIENCE INNOVATIVE THINKERS AND PRODUCTS



**ALL ABOUT EXPERIENCE** allpumps.com.au

1300 255 786 | sales@allpumps.com.au