## **Check and Rotary Valve Pumps**



# **SV-QD** Series

#### **Dispense Volume** 0-40ml

Viscosity (Check Valve) Low to Medium (<20,000 cps) Without Particles

Viscosity (Rotary Valve) Medium to High (>20,000 cps) With or Without Particles


#### **Applications**

Used in the Food, Pharmaceutical, and Cosmetic Industries, the SV-QD Series is easy to take apart and quickly to clean.



### **Details**

Servo Drive



Configurable Inlet & **Outlet Fittings** Pneumatic or Easy Dismantle Precision Volumetric Easy Clean Adjustment **High Accuracy 316L Stainless Steel Construction** +/- 0.5% or Better Other Materials of Construction

Available

Servo Drive Available Heated Pump options available

CV & RV Pump Models		Maximum Dispensing	Piston Stroke		Piston Diameter		Cycle Speed	Air Consumption	Weight		
	Pneumatic	Electric	Volume (cc)	mm	inch	mm	inch	(cpm) <sup>A</sup>	scfm (l/min) <sup>8</sup>	lbs (kg) <sup>c</sup>	
SV-QD7C			7.2			19.05	0.75	0.450Å	4.5.(40) <sup>B</sup>		
SV-QD10C			9.8	25.4	1	22.20	0.875				
SV-QD14C			14.5 27.00 1.062	0-150 <sup>^</sup>	1.5 (43) <sup>8</sup>	9 (2.6)					
SV-QD20C		E	20.1	25.4	1					8 (3.6)	
SV-QD30C	1		30.0	38.1	1.5	31.80	1.25	1.25 0-125 <sup>4</sup>	2.3 (65) <sup>8</sup>		
SV-QD40C	Р		40.0	50.8	2				3.1 (87) <sup>8</sup>		
SV-QD7R	۲		7.2		25.4 1	19.05	0.75	0.4000	1.9 (454) <sup>8</sup>	9.5 (4.3)	
SV-QD10R			9.8	25.4		22.20	0.875				
SV-QD14R	1		14.5			27.00 1	1.062	0-120 <sup>A</sup>			
SV-QD20R			20.1	25.4	1						
SV-QD30R			30.0	38.1	1.5	31.80	1.25	0.4004	2.7 (75) <sup>8</sup>		
SV-QD40R			40.0	50.8	2			0-100^	3.4 (97) <sup>8</sup>		

<sup>A</sup> Depending on the application, the maximum cycle rate will vary <sup>B</sup> Calculated at full stroke at 100cpm, 75 PSI (5 Bar) <sup>C</sup> Pneumatic Drive Only

## **Check and Rotary Valve Pumps**

# **SV-QD** Series




Fittings							
Туре	Size						
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Inlet	Outlet					
Sanitary	1/2″ - 3/4″	1/2″ - 3/4″					
Swage	1/8" - 1/2"	1/8" - 3/8"					
Tube	1/8" - 1/2"	1/8" - 3/8"					
Hose	1/2″ - 3/4″	1⁄2″ - 5/8″					


O-rings & U-cups							
0-rings	U-cup Seals						
Viton	Teflon						
EP	UHMW						
Silicon							
Buna							
Perfluor (Kalrez ®)							

Special sizes and metric available upon request

**Check Valve** 







CV & RV Pump Models		Maximum Dispensing	External Dimensions (Inches[Metric])							
	Pneumatic	Electric	Volume (cc)	A	В	С	D	E	F	G
SV-QD7C		E	7.2	1.94 [49]	3.70 [94]	10.5 [267]	3.2 [81]	1.2 [30]	1.5 [38]	8-32 UNC
SV-QD10C			9.8							
SV-QD14C			14.5							
SV-QD20C			20.1							
SV-QD30C			30.0			14.7 [374]				
SV-QD40C	Р		40.0			16.2 [411]				
SV-QD7R	۲		7.2	3.65 [93]	3.70 [94]	10.9 [275]	3.2 [81]	1.2 [30]	1.5 [38]	8-32 UNC
SV-QD10R			9.8							
SV-QD14R			14.5							
SV-QD20R			20.1							
SV-QD30R			30.0			15 [382]				
SV-QD40R			40.0			16.5 [419]				

н



### Contact Us:

Asia: <u>sales@hife-battery.com</u> – North America: <u>sales.1@hife-canada.com</u> Europe: <u>sales@hife-europe.com</u> – South America: <u>sales@hife-brasil.com</u>